

# <u>HY1X04</u>

### **FEATURES**

- Outward Swinging Waterproof 24 3/8" walk-in door
- Comfortable deep molded seat and luxurious head rest pillow
- Left/Right Models Available
- Comfortable arm support
- Easy installation (4-6 hours)
- ❖ Free Standing or Built in
- Matte finish
- Safety grab bar & Tub Fill
- Water Temperature Controls
- Accessory rack
- Hand held shower
- Interior access panel
- Drain access panel
- Factory tested

#### Available in three versions:

HY-1104 – 8 whirlpool jets with built-in heater

HY-1204 – 16 heated air jets

HY-1304 - simple soaking tub

### **TECHNICAL INFORMATION**

Materials: Acrylic composite
Power Supply: 110V
Dimensions: 51x29x42
Water Usage: 55-65 gallons

• Drain capacity: 40 gallons per minute

## PLUMBING REQUIREMENTS

- Unit is equipped with flexible, metal braided ½ inch water supply hose with ½ female threaded connectors
- Need to install hot and cold shutoffs with ½ male threaded nipples (not included)
- It is advised to have tub onsite before preparing drain location.
- <u>Note:</u> The flexible drain hose that is included with this unit is for installation into a floor drain only. Substituting the existing drain show for a different one will not void the warranty as long as there is no damage or evidence of misuse.

# **ELECTRICAL INFORMATION FOR HEATED AIR PUMP (HY 1204)**

- Air jet motor with heater 110 volt
- Dedicated 12-2 wire with 110 volt, 15-20 amp GFCI breaker

# ELECTRICAL INFORMATION FOR SYLLENT BRAND WATER PUMP (HY 1104)

- 3/4 HP water pump with internal heater
- 12-2 wire with 110 volt, 20 amp GFCI breaker
- Energy efficient pump

## **GENERAL INFORMATION**

<u>Note</u>: It is advised to have the tub onsite before preparing drain location.
Unit <u>must</u> be leveled in its permanent position and all feet must be on the ground to fully support the tub <u>Manufacturer</u> reserves the right to change specs or features at anytime. Please check to confirm details. 1-866-783-2661

# **Left Hand**

# **Right Hand**

