



Right model shown

M6028

FEATURES

- ❖ Black & Clear tempered glass walls
- ❖ Phone & FM Radio
- ❖ Auxiliary RCA input
- ❖ Steam Aromatherapy Cup
- ❖ Body Massage Jets
- ❖ Rainfall Shower Head
- ❖ Hand-held Shower w/ Height-Adjustable Bracket
- ❖ 2 Removable Benches
- ❖ Adjustable Steam Time & Temperature Settings
- ❖ Control Panel with Remote
- ❖ Hinged Door
- ❖ Circulation Fan
- ❖ Chromatherapy lighting
- ❖ 3kW Self-Cleaning Steam Generator
- ❖ Stone composite base
- ❖ Assembly from inside the unit

TECHNICAL INFORMATION

- **Materials:** Tempered Glass
- **Power Supply:** 220V
- **Steam Ready:** 2-5 MIN
- **Dimensions:** 59 x 40 x 84 IN

ELECTRICAL INFORMATION

- 1 dedicated 12-2 line for steam (line 1, line 2, and ground)
- 220 volt, 20 amp GFCI breaker
- There is a length of wire from the main control box supplied to connect to power source.

PLUMBING REQUIRMENTS

- The unit is equipped with hot and cold, metal braided ½ inch water supply hose with ½ national pipe thread.
- Need to install hot and cold shutoffs with ½ -male national pipe thread (not included).
- Supply hoses are to connect from the faucet manifold on the unit to the shutoff valves.
- All water jet features are pre plumbed with reinforced braided flexible supply hose
- All fixtures and fittings must be checked for tightness as they may have been loosened during transport. It is advised to have base onsite before preparing drain location.
- Please contact Steam Planet for special instructions regarding connection of the steam generator drain and steam cup drain to the main drain.

GENERAL INFORMATION

- Units come broken down in panels and are assembled with screws, nuts and bolts on site.
- This unit assembles from the -inside for convenience.
- **Note:** All shower bases are a man made stone composite and may need to be set in mortar for leveling purposes. It is advised to have base onsite before preparing drain location.
- Access panel near controls panel and jets recommended.
- **Manufacturer reserves the right to change specs or features at anytime. Please check to confirm details.**
1-866-783-2661

M6028R



M-6028-L

